



Safety, Efficient & Earth friendly

AC/DC Adaptor 24W Series Wall Mount

UUx Series

Product Highlights:

- ✓ Stability
- ✓ small size
- ✓ Cost efficiency
- ✓ Available at Japan, Taiwan, USA, Europe & UK type
- ✓ Suit Portable HDD, Portable GPS, PDA & network device

Protection:

- ✓ Short circuit protection
- ✓ Over Voltage Protection
- ✓ Over Current Protection

Efficiency:

- ✓ CEC Leve 5



Safety Approvals:

- ✓ UL60950
- ✓ CAN/CSA C22.2 NO. 60950
- ✓ EN60950-1
- ✓ CE (Low Voltage Directive)
- ✓ PSE
- ✓ CEC-400
- ✓ IEC 60950
- ✓ CNS14336
- ✓ GB4943.1

Emissions:

- ✓ CE CISPR 22 Class B
- ✓ VCCI Class B
- ✓ CNS13438 Class B
- ✓ FCC Part15 Class B

Immunity:

- ✓ EN55024/A1:2001
- ✓ Electrostatic discharge: 61000-4-2
- ✓ Radiated electromagnetic fields:61000-4-3
- ✓ Fast transients (Burst): 61000-4-4
- ✓ Surge transients: 61000-4-5
- ✓ Conducted disturbance: 61000-4-6
- ✓ Voltage dips, interruptions & Variations:61000-4-11

Electrical Spec:

Absolute Maximum Rating

| Input | | | | | |
|-------------|-----|---------|-----|-------|-----------------------------|
| Description | Min | Typ | Max | Units | Comment |
| Voltage | 90 | 120/240 | 264 | VAC | 2 Wire No Protection Ground |
| Frequency | 47 | 50/60 | 63 | Hz | |

| Environmental | | | | | |
|--------------------------|-----|-----|-----|-------|---------------------------|
| Description | Min | Typ | Max | Units | Comment |
| Operating Temperature | 0 | - | 40 | °C | Free Convection,Sea level |
| Non-Operating Temperture | -20 | - | 65 | °C | Free Convection,Sea level |
| Operating Humidity | 10 | - | 90 | %RH | No Condensing |
| Non-Operating Humidity | 10 | - | 90 | %RH | No Condensing |

Typical model list:

AC/DC Adaptor 24W Series Wall Mount

| Input Condition | DC Output Voltage | DC Output Current | Output Voltage Precision | Ripple & Noises | Regulation | | Option/Remark | |
|---|-------------------|-------------------|--------------------------|-----------------|------------|------|---------------|---|
| | | | | | Line | Load | | |
| Input Voltage: 90V-264Vac Frequency: 47-63Hz | 1 | 5V | 2.0A | ±5% | 100mV | ±1% | ±5% | |
| | 2 | 5V | 3.0A | ±5% | 100mV | ±1% | ±5% | |
| | 3 | 12V | 1.25A | ±5% | 200mV | ±1% | ±3% | |
| | 4 | 12V | 1.5A | ±5% | 200mV | ±1% | ±3% | |
| | 5 | 12V | 2.0A | ±5% | 200mV | ±1% | ±3% | |
| | 6 | 24V | 1.0A | ±5% | 300mV | ±1% | ±2% | |
| | 7 | - | - | - | - | - | - | - |


Measurement condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.
2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec:

| UU | UUZ Series | UUE | UUR Series | UUK Series |
|----|------------|-----|------------|------------|
| | | | | |
| | | | | |

| UUA Series | UUG Series | UUF Series |
|------------|------------|------------|
| | | |



Packing Spec:

| Type | Pcsper Carton | Gross Weight (kg) | Net Weihgt(kg) | Size(mm) | CBM(m2) | Container | Ctn/Contai ner | Pcs/Contai ner | Gross Weingt (Ton) | Remark |
|---------|---------------|-------------------|----------------|-------------|---------|-----------|----------------|----------------|--------------------|---------------|
| UU | 63 | 9.69 | 8.19 | 406x250x298 | 1x1.2 | 20 | 800 | 50400 | 7992 | With Gift Box |
| | 100 | 16 | 13 | 565x393x255 | 1x1.2 | 20 | 400 | 40000 | 6640 | Bulk package |
| UUE/UUF | 42 | 7.254 | 5.754 | 406x250x298 | 1x1.2 | 20 | 800 | 33600 | 6043.2 | With Gift Box |
| | 60 | 11.22 | 8.22 | 565x393x255 | 1x1.2 | 20 | 400 | 24000 | 4728 | Bulk package |
| UUK | 42 | 7.38 | 5.88 | 406x250x298 | 1x1.2 | 20 | 800 | 33600 | 6144 | With Gift Box |
| | 60 | 11.4 | 8.4 | 565x393x255 | 1x1.2 | 20 | 400 | 24000 | 4800 | Bulk package |
| UUA/UUG | 42 | 7.38 | 5.88 | 406x250x298 | 1x1.2 | 20 | 800 | 33600 | 6144 | With Gift Box |
| | 60 | 11.4 | 8.4 | 565x393x255 | 1x1.2 | 20 | 400 | 24000 | 4800 | Bulk package |