




Safety , Efficient & Earth friendly

USB AC/DC Adaptor 25W Series

UWB(4Port) Series



Product Highlights:

- ✓ Portable
- ✓ Compact size
- ✓ Availabel at Japan, Taiwan, US type
- ✓ Suit SMART PHONE, TABLET, and most USB device

Protection:

- ✓ Short circuit protection
- ✓ Over Voltage Protection
- ✓ Over Current Protection

Efficiency:

- ✓ DOE Level 6

Safety Approvals:

- ✓ PSE
- ✓ CEC-400
- ✓ CE (Low Voltage Directive)

Emissions:

- ✓ CE CISPR 22 Class B

Immunity:

- ✓ EN55024/A1:2001
- ✓ Electrostatic discharge: 61000-4-2
- ✓ Radiated electromagnetic fields:61000-4-3
- ✓ Fast transients (Burst): 61000-4-4
- ✓ Surge transients: 61000-4-5
- ✓ Conducted disturbance: 61000-4-6
- ✓ Voltage dips, interruptions & Variations:61000-4-11

Electrical Spec:

Absolute Maximum Rating

Input					
Description	Min	Typ	Max	Units	Comment
Voltage	90	120/240	264	VAC	2 Wire No Protection Ground
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min	Typ	Max	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection,Sea level
Non-Operating Temperture	-20	-	65	°C	Free Convection,Sea level
Operating Humidity	10	-	90	%RH	No Condensing
Non-Operating Humidity	10	-	90	%RH	No Condensing

USB AC/DC Adaptor 24W Series


Typical model list:

Input Condition		DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noises	Regulation		Option/Remark
							Line	Load	
Input Voltage: 90V-264Vac Frequency: 47-63Hz	1	5V	4.2A	±5%	100mV	200mV	±1%	±5%	
	2	-	-	-	-	-	-	-	-

Measurement condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.
2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec:



Packing Spec:

Type	Pcsper Carton	Gross Weight (kg)	Net Weight(kg)	Size(mm)	CBM(m2)	Container	Ctn/Container	Pcs/Container	Gross Weight (Ton)	Remark
UWB325-USB4	84	9.2	7.7	406x250x298	1x1.2	20	800	67200	7600	With Gift Box