

MODEL NO: UNOWT3075-240032SA

24V/3.2A

Temperature increase of components (主要部品温度上升)

※Character Condition(特性条件):

1	I/P Voltage(Vac)(輸入電壓)	100Vac/240Vac
2	I/P Frequency(Hz)(輸入頻率)	50Hz /60Hz
3	Output Load(輸出負載)	Full Load
4	Ambient Temp.(°C)(環境溫度)	40.0°C
5	Sample Size(取樣數)	1PCS
6	Mounting Method(取付方法)	Mounting A

※Character Data (特性數據):

Location	Description	ΔT Temperature Rise (°C)	
		100Vac/60Hz	240Vac/50Hz
C1	E-CAP	37.70	28.90
C1A	E-CAP	44.90	36.70
C5	E-CAP	38.60	37.70
C22	E-CAP	37.10	37.50
C23	E-CAP	34.10	32.90
Q11	MOSFET	56.90	49.60
Q21	SCHOTTKY	54.20	49.20
D21	SCHOTTKY	54.30	49.40
D3	DIODE	67.20	57.00
D4	DIODE	52.00	44.40
T1	Transformer-Coil	56.50	51.70
U1	PWM Power Switch IC	55.10	47.20
LF1	Common Choke	38.90	23.70
LF2	Common Choke	34.30	32.20
BD1	Bridge Diode	51.80	41.40

CN1(INPUT)

