


UOA Series

Open Frame Switching Power Supply **45W** Series



▲ UOA345



■ Please contact our sales department for safety standard of each model.



Product Highlights

- Stability
- Ultra small size
- Energy efficiency

Protection

- Short circuit protection
- Over Voltage Protection
- Over Current Protection
- Over Temperature Protection

Safety Approvals

- IEC/EN60950-1

Emissions

- CE CISPR 32 Class B

Immunity

- EN55024/A1:2001

Input					
Description	Min	Typ	Max	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min	Typ	Max	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection, Sea level
Storage Temperature	-20	-	65	°C	Free Convection, Sea level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing

Typical model list


Input Condition		DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noises	Regulation		Option/Remark
							Line	Load	
Input Voltage: 90V-264Vac Frequency: 47-63Hz	1	12.0V	4.0A	±5%	120mV	120mV	2%	10%	
	2	15.0V	3.0A	±5%	150mV	150mV	2%	10%	
	3	24.0V	2.0A	±5%	240mV	240mV	2%	10%	
	4	35.0V	1.3A	±5%	300mV	300mV	2%	10%	
	5	-	-	-	-	-	-	-	

■ Measurement condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.

2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec



■ Please contact our sales department for details of each model ■