

SU 12W Series

-20°C/+60°C Wide Operating Temperature Range AC/DC Adaptor



▲ **SU318**



▲ **SUZ318**



▲ **SUE318**



▲ **SUA318**



▲ **SUK318**



▲ **SUR318**



▲ **SUL318**



▲ **SUF318**



▲ **SUG318**



■ All safety meets 40 degree standard.
■ Please contact our sales department for safety standard of each model.



Product Highlights

- -20°C~60°C Operating Temperature for 12W
- Stability
- Small Size
- Cost Efficiency
- Suit Portable HDD, Portable GPS, PDA & Network Device

Efficiency

- COMMISSION REGULATION (EU) 2019/1782 (ERP 6)& DOE 6

Protection

- Short Circuit Protection
- Over Voltage Protection
- Over Current Protection

Emissions

- FCC Part15 Class B
- CE CISPR 32 EN55032
- VCCI Class B
- GB9254/GB17625.1

Safety Standard

- 60950-1
- 62368-1
- GB4943.1
- PSE 別表第八

Immunity

- EN55024/A1:2001

Input					
Description	Min.	Typ.	Max.	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min.	Typ.	Max.	Units	Comment
Operating Temperature for 18W	0	-	40	°C	Free Convection,Sea Level
Operating Temperature for 12W	-20	-	60	°C	Free Convection,Sea Level
Storage Temperature	-20	-	65	°C	Free Convection,Sea Level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing

Typical model list

No.		DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noise	Average Active Efficiency	No-Load Power Consumption	Option/Remark
1	SU318-0530	5.0V	2.0A	±5%	150mV	150mV	78.70%	0.1W	-20°C~60°C
		5.0V	3.0A	±5%	150mV	150mV	81.39%	0.1W	0°C~40°C
2	SU318-5925	5.9V	2.0A	±5%	150mV	150mV	79.83%	0.1W	-20°C~60°C
		5.9V	2.5A	±5%	150mV	150mV	81.28%	0.1W	0°C~40°C
3	SU318-0920	9.0V	1.45A	±5%	200mV	240mV	83.41%	0.1W	-20°C~60°C
		9.0V	2.0A	±5%	200mV	240mV	85.00%	0.1W	0°C~40°C
4	SU318-1215	12.0V	1.0A	±5%	150mV	240mV	82.96%	0.1W	-20°C~60°C
		12.0V	1.5A	±5%	150mV	240mV	85.00%	0.1W	0°C~40°C
5	SU318-1512	15.0V	0.8A	±5%	200mV	300mV	82.96%	0.1W	-20°C~60°C
		15.0V	1.2A	±5%	200mV	300mV	85.00%	0.1W	0°C~40°C
6	SU318-2475	24.0V	0.5A	±5%	240mV	480mV	82.96%	0.1W	-20°C~60°C
		24.0V	0.75A	±5%	240mV	480mV	85.00%	0.1W	0°C~40°C
7	SU318-4804	48.0V	0.25A	±5%	480mV	480mV	82.96%	0.1W	-20°C~60°C
		48.0V	0.4A	±5%	480mV	480mV	85.00%	0.1W	0°C~40°C

■ Measurement Condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.
2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.
- Precaution The different output current is applied to the different operating temperature. For example, 12.0V/1.0A is for -20°C to 60°C and 12.0V/1.5A is for 0°C to 40°C. For the applicable safety standards, see the specification sheef.
3. Safety certificates were available for the model with 0~40 degrees operation.
No certificates for the model which operating under -20~60 degrees,but the design can meet safety standard.

more detail on next page

SU318 Series	SUZ318 Series
<p>Front view, Top view (70.00, 35.00), and Side view (48.00) of the SU318 Series.</p>	<p>Front view, Top view (70.00, 35.00), and Side view (48.00) of the SUZ318 Series.</p>
SUE318 Series	SUA318 Series
<p>Front view, Top view (70.00, 35.00), and Side view (66.30) of the SUE318 Series.</p>	<p>Front view, Top view (70.00, 35.00), and Side view (57.00) of the SUA318 Series.</p>
SUK318 Series	SUR318 Series
<p>Front view, Top view (70.00, 48.80), and Side view (55.20) of the SUK318 Series.</p>	<p>Front view, Top view (70.00, 35.00), and Side view (66.30) of the SUR318 Series.</p>

SUL318 Series	SUF318 Series
SUG318 Series	

————— the following blank —————

■ Please contact our sales department for details of each model ■