

UN 60W Series

I.T.E./AV AC/DC Adaptor



▲ **UNI360**



▲ **UNB360**



▲ **UNC360**



■ Please contact our sales department for safety standard of each model.



Product Highlights

- Stability
- Compact Size
- Energy Efficiency
- Suit LCD Display, Hand Held Computer, Multimedia Player, etc

Protection

- Short Circuit Protection
- Over Voltage Protection
- Over Current Protection

Safety Standard

- 60950-1
- 62368-1
- TP TC 004/2011
- PSE 別表第八

Efficiency

- Energy Efficiency Level VI (ErP / DoE)
- Meet COMMISSION REGULATION(EU) 2019/1782
- Meet DOE 10 CFR part 429 and 430

Emissions

- FCC Part15 Class B
- CE CISPR 32 EN55032
- VCCI Class B
- TP TC 020/2011
- BS EN55032

Immunity

- EN 55035
- BS EN55035

Input					
Description	Min.	Typ	Max.	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min.	Typ.	Max.	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection,Sea Level
Storage Temperature	-20	-	65	°C	Free Convection,Sea Level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing

Typical model list

No.	DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noise	Average Active Efficiency	No-Load Power Consumption	Option/Remark
1	12.0V	4.0A	±5%	300mV	300mV	87.77%	0.1W	
2	12.0V	4.2A	±5%	300mV	300mV	88.00%	0.21W	
3	12.0V	5.0A	±5%	360mV	480mV	88.00%	0.21W	
4	13.0V	4.0A	±5%	300mV	600mV	89.00%	0.15W	
5	15.0V	4.0A	±5%	300mV	300mV	88.00%	0.21W	
6	16.0V	3.75A	±5%	300mV	300mV	88.00%	0.21W	
7	18.0V	3.33A	±5%	360mV	480mV	88.00%	0.21W	
8	24.0V	2.5A	±5%	240mV	480mV	88.00%	0.21W	
9	48.0V	1.25A	±5%	480mV	480mV	82.96%	0.21W	

■ Measurement Condition

- Measurements shall be made with an oscilloscope with 20MHz bandwidth.
- Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec

UNI360 Series	UNB360 Series	UNC360 Series

■ Please contact our sales department for details of each model ■