

UN 90W Series

UNIFIVE
2023.11.02 V3


I.T.E./AV AC/DC Adaptor




▲ UNI390



▲ UNB390



■ Please contact our sales department for safety standard of each model.



Product Highlights

- Stability
- Energy Efficiency
- Suit LCD Display, Laptop Computer, Multimedia Player, etc.

Protection

- Short Circuit Protection
- Over Voltage Protection
- Over Current Protection
- Over Temperature Protection (Optional)

Safety Standard

- 60950-1
- 62368-1
- PSE 別表第八

Efficiency

- Energy Efficiency Level VI (ErP / DoE)
- Meet COMMISSION REGULATION(EU) 2019/1782
- Meet DOE 10 CFR part 429 and 430

Emissions

- FCC Part15 Class B
- CE CISPR 32 EN55032
- VCCI Class B
- KN32 KN35
- BS EN55032

Immunity

- EN 55035
- BS EN55035

Input					
Description	Min.	Typ.	Max.	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	
Power Factor	ACIN 100V	0.9	-	-	-
	ACIN 230V	0.9	-	-	-

Environmental					
Description	Min.	Typ.	Max.	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection, Sea Level
Storage Temperature	-20	-	65	°C	Free Convection, Sea Level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing

Typical model list

No.	DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noise	Average Active Efficiency	No-Load Power Consumption	Option/Remark
1	12.0V	7.5A	±5%	120mV	240mV	88.00%	0.21W	
2	13.5V	6.7A	±5%	360mV	480mV	82.96%	0.1W	
3	15.0V	6.0A	±5%	360mV	480mV	88.00%	0.21W	
4	19.0V	4.73A	±5%	190mV	380mV	88.00%	0.21W	
5	20.0V	4.5A	±5%	240mV	480mV	88.00%	0.1W	
6	24.0V	3.75A	±5%	240mV	480mV	88.00%	0.21W	

■ Measurement Condition

- Measurements shall be made with an oscilloscope with 20MHz bandwidth.
- Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec

UNI390 Series	UNB390 Series

■ Please contact our sales department for details of each model ■